

Package ‘DSI’

March 15, 2021

Type Package

Title 'DataSHIELD' Interface

Version 1.2.0

Description 'DataSHIELD' is an infrastructure and series of R packages that enables the remote and 'non-disclosive' analysis of sensitive research data. This package defines the API that is to be implemented by 'DataSHIELD' compliant data repositories.

Depends R (>= 3.1),
methods,
progress,
R6

Suggests testthat (>= 2.1.0)

License LGPL (>= 2.1)

URL <http://datashield.ac.uk>

BugReports <https://github.com/datashield/DSI>

RoxygenNote 7.1.1

Encoding UTF-8

LazyData true

Collate 'DSObject.R'
'hidden.R'
'DSConnection.R'
'DSDriver.R'
'DSLoginBuilder.R'
'DSResult.R'
'datashield.aggregate.R'
'datashield.assign.R'
'datashield.connections.R'
'datashield.errors.R'
'datashield.list.R'
'datashield.login.R'
'datashield.logout.R'
'datashield.status.R'

'datashield.symbol.R'
 'datashield.workspace.R'
 'rd.R'
 'utils.R'

R topics documented:

datashield.aggregate	3
datashield.assign	4
datashield.assign.expr	5
datashield.assign.resource	6
datashield.assign.table	7
datashield.connections	8
datashield.connections_default	9
datashield.connections_find	10
datashield.errors	11
datashield.login	11
datashield.logout	13
datashield.methods	14
datashield.method_status	14
datashield.pkg_check	15
datashield.pkg_status	15
datashield.resources	16
datashield.resource_status	16
datashield.rm	17
datashield.symbols	17
datashield.tables	18
datashield.table_status	18
datashield.workspaces	19
datashield.workspace_rm	19
datashield.workspace_save	20
dsAggregate	20
dsAssignExpr	21
dsAssignResource	22
dsAssignTable	23
dsConnect	24
DSCConnection-class	25
dsDisconnect	25
DSDriver-class	26
dsFetch	26
dsGetInfo	27
dsHasResource	28
dsHasTable	29
dsIsAsync	29
dsIsCompleted	30
dsKeepAlive	31
dsListMethods	32
dsListPackages	33

datashield.aggregate 3

dsListResources	33
dsListSymbols	34
dsListTables	35
dsListWorkspaces	36
DSLoginBuilder	36
DSSObject-class	38
DSSResult-class	39
dsRmSymbol	39
dsRmWorkspace	40
dsSaveWorkspace	41
newDSLoginBuilder	42

Index 43

datashield.aggregate *Data aggregation*

Description

Aggregates the expression result using the specified aggregation method in the current Datashield session.

Usage

```
datashield.aggregate(conns, expr, async = TRUE)
```

Arguments

conns	DSConnection-class object or a list of DSConnection-class s.
expr	Expression to evaluate.
async	Whether the result of the call should be retrieved asynchronously. When TRUE (default) the calls are parallelized over the connections, when the connection supports that feature, with an extra overhead of requests.

Value

The result of the aggregation

Examples

```
## Not run:  
# call aggregate function on server side  
datashield.aggregate(conns, expr = quote(someFunction(D, 123)))  
  
# call aggregate functions that are defined in the provided named list.  
# Connections are filtered by the list names.  
datashield.aggregate(conns,  
  list(server1=quote(someFunction(D, 123)), server2=quote(someFunction(G, 456)))
```

```
## End(Not run)
```

```
datashield.assign    Data assignment
```

Description

Assign a table or an expression result to a R symbol in the Datashield R session.

Usage

```
datashield.assign(
  conns,
  symbol,
  value,
  variables = NULL,
  missings = FALSE,
  identifiers = NULL,
  id.name = NULL,
  async = TRUE
)
```

Arguments

conns	DSConnection-class object or a list of DSConnection-class s.
symbol	Name of the R symbol.
value	Fully qualified name of a table reference in data repositories (see datashield.assign.table for more details) or a R expression with allowed assign functions calls.
variables	List of variable names or Javascript expression that selects the variables of a table (ignored if value does not refer to a table). See javascript documentation: http://opaldoc.obiba.org/en/latest/magma-user-guide/variable/
missings	If TRUE, missing values will be pushed from data repository to R, default is FALSE. Ignored if value is an R expression.
identifiers	Name of the identifiers mapping to use when assigning entities to R (if supported by data repository).
id.name	Name of the column that will contain the entity identifiers. If not specified, the identifiers will be the data frame row names. When specified this column can be used to perform joins between data frames.
async	Whether the result of the call should be retrieved asynchronously (TRUE means that calls are parallelized over the connections, when the connection supports that feature, with an extra overhead of requests).

Examples

```
## Not run:
# assign a list of variables from table HOP
datashield.assign(conn, symbol="D", value="demo.HOP",
  variables=list("GENDER","LAB_GLUC"))

# assign all the variables matching 'LAB' from table HOP
datashield.assign(conn, symbol="D", value="demo.HOP",
  variables="name().matches('LAB_')")

## End(Not run)
```

```
datashield.assign.expr
```

Expression result assignment

Description

Assign the result of the execution of an expression to a R symbol in the Datashield R session.

Usage

```
datashield.assign.expr(conns, symbol, expr, async = TRUE)
```

Arguments

conns	DSConnection-class object or a list of DSConnection-class s.
symbol	Name of the R symbol.
expr	R expression with allowed assign functions calls.
async	Whether the result of the call should be retrieved asynchronously. When TRUE (default) the calls are parallelized over the connections, when the connection supports that feature, with an extra overhead of requests.

Examples

```
## Not run:
# assign an expression to G
datashield.assign.expr(conns, symbol = "G", expr = quote(as.numeric(D$GENDER)))

# assign the expressions that are defined in the provided named list.
# Connections are filtered by the list names.
datashield.assign.expr(conns, "G",
  list(server1=quote(as.numeric(D$GENDER)), server2=quote(as.numeric(D$SEX))))

## End(Not run)
```

`datashield.assign.resource`*Resource assignment*

Description

Assign a resource object of class 'ResourceClient' to a R symbol in the Datashield R session.

Usage

```
datashield.assign.resource(conns, symbol, resource, async = TRUE)
```

Arguments

<code>conns</code>	DSConnection-class object or a list of DSConnection-classes .
<code>symbol</code>	Name of the R symbol.
<code>resource</code>	Fully qualified name of a resource reference in the data repository (can be a vector or must be the same in each data repository); or a named list of fully qualified resource names (one per server name); or a data frame with 'server' and 'resource' columns (such as the one that is used in datashield.login)
<code>async</code>	Whether the result of the call should be retrieved asynchronously. When TRUE (default) the calls are parallelized over the connections, when the connection supports that feature, with an extra overhead of requests.

Examples

```
## Not run:
# assign a resource HOP
datashield.assign.resource(conn, symbol="rsrc", resource="demo.HOP")

# assign the tables that are defined in the logindata ('server' and 'resource' columns are
# expected) data frame that is used in datashield.login() function. Connections names
# and server names must match.
datashield.assign.resource(conns, "rsrc", logindata)

# assign the resources that are defined in the provided named list.
# Connections are filtered by the list names.
datashield.assign.resource(conns, "rsrc",
  list(server1="datashield.CNSIM1", server2="datashield.CNSIM2"))

## End(Not run)
```

`datashield.assign.table`*Table assignment*

Description

Assign a table to a R symbol in the Datashield R session.

Usage

```
datashield.assign.table(  
  conns,  
  symbol,  
  table,  
  variables = NULL,  
  missings = FALSE,  
  identifiers = NULL,  
  id.name = NULL,  
  async = TRUE  
)
```

Arguments

<code>conns</code>	<code>DSConnection-class</code> object or a list of <code>DSConnection-class</code> s.
<code>symbol</code>	Name of the R symbol.
<code>table</code>	Fully qualified name of a table in the data repository (can be a vector or must be the same in each data repository); or a named list of fully qualified table names (one per server name); or a data frame with 'server' and 'table' columns (such as the one that is used in <code>datashield.login</code>)
<code>variables</code>	List of variable names or Javascript expression that selects the variables of a table. See javascript documentation: http://opaldoc.obiba.org/en/latest/magma-user-guide/variable/
<code>missings</code>	If TRUE, missing values will be pushed from data repository to R, default is FALSE. Ignored if value is an R expression.
<code>identifiers</code>	Name of the identifiers mapping to use when assigning entities to R (if supported by the data repository).
<code>id.name</code>	Name of the column that will contain the entity identifiers. If not specified, the identifiers will be the data frame row names. When specified this column can be used to perform joins between data frames.
<code>async</code>	Whether the result of the call should be retrieved asynchronously. When TRUE (default) the calls are parallelized over the connections, when the connection supports that feature, with an extra overhead of requests.

Examples

```

## Not run:
# assign a list of variables from table HOP
datashield.assign.table(conn, symbol="D", table="demo.HOP",
  variables=list("GENDER","LAB_GLUC"))

# assign all the variables matching 'LAB' from table HOP
datashield.assign.table(conn, symbol="D", table="demo.HOP",
  variables="name().matches('LAB_')")

# assign the tables that are defined in the logindata ('server' and 'table' columns are
# expected) data frame that is used in datashield.login() function. Connections
# are filtered by the list names.
datashield.assign.table(conns, "D", logindata)

# assign the tables that are defined in the provided named list.
# Connections are filtered by the list names.
datashield.assign.table(conns, "D", list(server1="datashield.CNSIM1", server2="datashield.CNSIM2"))

## End(Not run)

```

datashield.connections

List the DSConnection objects in the analytic environment

Description

This function identifies and prints all [DSConnection-class](#) objects in the analytic environment. If there are no DSConnection servers in the analytic environment [datashield.connections](#) reminds the user that they have to login to a valid set of DataSHIELD aware servers. If there is only one set of DSConnections, it copies that one set and names the copy 'default.connections'. This default set will then be used by default by all subsequent calls to client-side functions. If there is more than one set of DSConnections in the analytic environment, [datashield.connections](#) tells the user that they can either explicitly specify the DSConnections to be used by each client-side function by providing an explicit "datasources=" argument for each call, or can alternatively use the [datashield.connections_default](#) function to specify a default set of DSConnections to be used by all client-side calls unless over-ruled by the 'datasources=' argument.

Usage

```
datashield.connections(env = getOption("datashield.env", globalenv()))
```

Arguments

env The environment where to search for the connection symbols. Try to get it from the 'datashield.env' option, with default to the Global Environment.

Value

Returns a list of [DSConnection-class](#) objects and advises the user how best to respond depending whether there are zero, one or multiple connections detected.

See Also

Other Connections management: [datashield.connections_default\(\)](#), [datashield.connections_find\(\)](#)

`datashield.connections_default`

Set or get the default list of DSConnection objects in the analytic environment

Description

By default if there is only one set of [DSConnection-class](#) objects that is available for analysis, all DataSHIELD client-side functions will use that full set of DSConnections unless the 'datasources=' argument has been set and specifies that a particular subset of those DSConnections should be used instead. The correct identification of the full single set of opals is based on the [datashield.connections_find](#) function. To illustrate, if the single set of Opals is called 'study.opals' and consists of six servers numbered studies[1] to studies[6] then all client-side functions will use data from all six of these 'studies' unless, say, `datasources=studies[c(2,5)]` is declared and only data from the second and fifth studies will then be used. On the other hand, if there is more than one set of DSConnections in the analytic environment client-side functions will be unable to determine which set to use. The function [datashield.connections_find](#) has therefore been written so that if one of the DSConnection sets is called 'default.connections' then that set - i.e. 'default.connections' - will be selected by default by all DataSHIELD client-side functions. If there is more than one set of DSConnections in the analytic environment and NONE of these is called 'default.connections', the function [datashield.connections_find](#) will fail. Therefore `datashield.connections_default` copies the provided set of DSConnections as 'default.connections'. This set will then be selected by default by all client-side functions, unless it is deleted and an alternative set of DSConnections is copied and named 'default.connections'. Regardless how many sets of DSConnections exist and regardless whether any of them may be called 'default.connections', the 'datasources=' argument overrides the defaults and allows the user to base his/her analysis on any set of DSConnections and any subset of those DSConnections.

Usage

```
datashield.connections_default(  
  name = NULL,  
  env = getOption("datashield.env", globalenv())  
)
```

Arguments

name	Symbol name that identifies the set of DSConnection-class objects to be used by default. If not provided, the 'default.connections' variable value is returned.
env	The environment where to search for the connection symbols. Try to get it from the 'datashield.env' option, with default to the Global Environment.

Value

The 'default.connections' value from the analytic environment or NULL if the 'default.connections' symbol is not defined.

See Also

Other Connections management: [datashield.connections_find\(\)](#), [datashield.connections\(\)](#)

datashield.connections_find

Search for DSConnection objects in the analytic environment

Description

If the user does not set the argument 'datasources' in the client side analysis functions, this function is called to search for [DSConnection-class](#) objects in the environment (default environment is the Global one). If one set of DSConnection objects is found, it is assigned to 'default.connections' symbol in the analytic environment. If more than one set of DSConnection objects is found and none of them is called 'default.connections', the function stops and suggests user to use the [datashield.connections_default](#) function.

Usage

```
datashield.connections_find(env = getOption("datashield.env", globalenv()))
```

Arguments

env	The environment where to search for the connection symbols. Try to get it from the 'datashield.env' option, with default to the Global Environment.
-----	---

Value

Returns a list of [DSConnection-class](#) objects or stops the process

See Also

Other Connections management: [datashield.connections_default\(\)](#), [datashield.connections\(\)](#)

datashield.errors	<i>List R last errors</i>
-------------------	---------------------------

Description

Get the R last errors available after the `datashield.assign` or `datashield.aggregate` calls in the Datashield R session.

Usage

```
datashield.errors()
```

datashield.login	<i>Logs in a DataSHIELD R sessions and optionally assigns variables to R</i>
------------------	--

Description

This function allows for clients to login to data repository servers and (optionally) assign all the data or specific variables from the data repositories tables to R data frames. The assigned dataframes (one for each data repository) are named 'D' (by default). Different login strategies are supported: using a certificate/private key pair (2-way SSL encryption mechanism), using user credentials (user name and password) or using a personal access token (could be combined with a user name, depending on the data repository system).

Usage

```
datashield.login(
  logins = NULL,
  assign = FALSE,
  variables = NULL,
  missings = FALSE,
  symbol = "D",
  id.name = NULL,
  opts = getOption("datashield.opts", list()),
  restore = NULL
)
```

Arguments

logins	A dataframe table that holds login details. This table holds five elements required to login to the servers where the data to analyse is stored. The expected column names are 'driver' (the <code>DSDriver-class</code> name, default is "OpalDriver"), 'server' (the server name), 'url' (the server url), 'user' (the user name or the certificate PEM file path), 'password' (the user password or the private key PEM file path), 'token' (the personal access token, ignored if 'user' is defined), 'table'
--------	---

(the fully qualified name of the table in the data repository), 'resource' (the fully qualified name of the resource reference in the data repository), 'options' (the SSL options). An additional column 'identifiers' can be specified for identifiers mapping (if supported by data repository). See also the documentation of the exemplar input table logindata for details of the login elements.

assign	A boolean which tells whether or not data should be assigned from the data repository table to R after login into the server(s).
variables	Specific variables to assign. If assign is set to FALSE this argument is ignored otherwise the specified variables are assigned to R. If no variables are specified (default) the whole data repository's table is assigned.
missings	If TRUE, missing values will be pushed from data repository to R, default is FALSE.
symbol	A character, the name of the data frame to which the data repository's table will be assigned after login into the server(s).
id.name	Name of the column that will contain the entity identifiers. If not specified, the identifiers will be the data frame row names. When specified this column can be used to perform joins between data frames.
opts	Default SSL options to be used in case it is not specified in the logins structure.
restore	The workspace name to restore (optional).

Value

object(s) of class DSCConnection

Examples

```
## Not run:

#### The below examples illustrate an analyses that use test/simulated data ####

# build your data.frame
builder <- newDSLoginBuilder()
builder$append(server="server1", url="https://opal-demo.obiba.org",
               table="datashield.CNSIM1", resource="datashield.CNSIM1r",
               user="dsuser", password="password",
               options="list(ssl_verifyhost=0,ssl_verifypeer=0)")
builder$append(server="server2", url="dslite.server",
               table="CNSIM2", resource="CNSIM2r", driver="DSLiteDriver")
builder$append(server="server3", url="https://molgenis.example.org",
               table="CNSIM3", resource="CNSIM3r", token="123456789", driver="MolgenisDriver")
builder$append(server="server4", url="dslite.server",
               table="CNSIM4", resource="CNSIM4r", driver="DSLiteDriver")
logindata <- builder$build()

# or load the data.frame that contains the login details
data(logindata)

# Example 1: just login (default)
connections <- datashield.login(logins=logindata)
```

```
# Example 2: login and assign the whole dataset
connections <- datashield.login(logins=logindata, assign=TRUE)

# Example 3: login and assign specific variable(s)
myvar <- list("LAB_TSC")
connections <- datashield.login(logins=logindata, assign=TRUE, variables=myvar)

# note that the assignment information can also be provided afterwards
builder <- newDSLoginBuilder()
builder$append(server="server1", url="https://opal-demo.obiba.org",
               user="dsuser", password="password")
builder$append(server="server2", url="https://opal-test.obiba.org",
               token="123456789")
logindata <- builder$build()
connections <- datashield.login(logins=logindata)
datashield.assign.table(connections, symbol = "D",
                        table = list(server1 = "CNSIM.CNSIM1",
                                     server2 = "CNSIM.CNSIM2"))
datashield.assign.resource(connections, symbol = "rsrc",
                           table = list(server1 = "res.CNSIM1",
                                         server2 = "res.CNSIM2"))

## End(Not run)
```

datashield.logout *Logout from DataSHIELD R sessions*

Description

Clear the Datashield R sessions and logout from DataSHIELD data repositories.

Usage

```
datashield.logout(conns, save = NULL)
```

Arguments

conns	DSConnection-class object or a list of DSConnection-classes .
save	Save datashield sessions on each DataSHIELD data repository (if feature is supported) with provided ID (must be a character string).

datashield.methods *List of DataSHIELD methods*

Description

Get the list of all the DataSHIELD methods from the different data repositories.

Usage

```
datashield.methods(conns, type = "aggregate")
```

Arguments

conns [DSConnection-class](#) object or a list of [DSConnection-classes](#).
type Type of the method: "aggregate" (default) or "assign".

Value

Methods details from all the servers.

datashield.method_status
 Status of the DataSHIELD methods

Description

Get the status of the DataSHIELD methods in the different data repositories to check if any method is missing.

Usage

```
datashield.method_status(conns, type = "aggregate")
```

Arguments

conns [DSConnection-class](#) object or a list of [DSConnection-classes](#).
type Type of the method: "aggregate" (default) or "assign".

Value

Methods availability on each server.

`datashield.pkg_check` *Check server-side package minimum version*

Description

Check for each of the server, accessible through provided [DSConnection-class](#) objects, whether the installed

Usage

```
datashield.pkg_check(  
  conns,  
  name,  
  version,  
  env = getOption("datashield.env", globalenv())  
)
```

Arguments

<code>conns</code>	DSConnection-class object or a list of DSConnection-classes .
<code>name</code>	The name of the server-side package.
<code>version</code>	The minimum package version number to be matched.
<code>env</code>	Environment where the package status result should be cached. Try to get it from the 'datashield.env' option, with default to the Global Environment.

`datashield.pkg_status` *Status of the DataSHIELD packages*

Description

Get the status of the DataSHIELD packages in the different data repositories to check if any package is missing.

Usage

```
datashield.pkg_status(conns)
```

Arguments

<code>conns</code>	DSConnection-class object or a list of DSConnection-classes .
--------------------	---

Value

Packages status for each server.

datashield.resources *List of the resources*

Description

Get the list of all the resources from the different data repositories.

Usage

```
datashield.resources(conns)
```

Arguments

conns [DSConnection-class](#) object or a list of [DSConnection-class](#)s.

Value

Resource unique names from all the servers.

Examples

```
## Not run:  
datashield.resources(conns)  
  
## End(Not run)
```

datashield.resource_status
Status of some resources

Description

Get whether some identified resources are accessible in each of the data repositories.

Usage

```
datashield.resource_status(conns, resource)
```

Arguments

conns [DSConnection-class](#) object or a list of [DSConnection-class](#)s.
resource Fully qualified name of a resource in the data repository (can be a vector or must be the same in each data repository); or a named list of fully qualified resource names (one per server name); or a data frame with 'server' and 'resource' columns (such as the one that is used in [datashield.login](#))

Value

Resource status for each server.

datashield.rm	<i>Remove a R symbol</i>
---------------	--------------------------

Description

Remove a symbol from the current Datashield session.

Usage

```
datashield.rm(conns, symbol)
```

Arguments

conns	DSConnection-class object or a list of DSConnection-classes .
symbol	Name of the R symbol.

datashield.symbols	<i>List R symbols</i>
--------------------	-----------------------

Description

Get the R symbols available after the datashield.assign calls in the Datashield R session.

Usage

```
datashield.symbols(conns)
```

Arguments

conns	DSConnection-class object or a list of DSConnection-classes .
-------	---

datashield.tables *List of the tables*

Description

Get the list of all the tables from the different data repositories.

Usage

```
datashield.tables(conns)
```

Arguments

conns [DSConnection-class](#) object or a list of [DSConnection-class](#)s.

Value

Table unique names from all the servers.

Examples

```
## Not run:  
datashield.tables(conns)  
  
## End(Not run)
```

datashield.table_status
 Status of some tables

Description

Get whether some identified tables are accessible in each of the data repositories.

Usage

```
datashield.table_status(conns, table)
```

Arguments

conns [DSConnection-class](#) object or a list of [DSConnection-class](#)s.
table Fully qualified name of a table in the data repository (can be a vector or must be the same in each data repository); or a named list of fully qualified table names (one per server name); or a data frame with 'server' and 'table' columns (such as the one that is used in [datashield.login](#))

Value

Table status for each server.

`datashield.workspaces` *List saved DataSHIELD R workspaces*

Description

Get the list of R workspaces that were saved during a Datashield R session.

Usage

`datashield.workspaces(conns)`

Arguments

`conns` [DSCConnection-class](#) object or a list of [DSCConnection-class](#).

`datashield.workspace_rm`
Remove a DataSHIELD workspace

Description

Remove in each data repository the workspace with the provided name.

Usage

`datashield.workspace_rm(conns, ws)`

Arguments

`conns` [DSCConnection-class](#) object or a list of [DSCConnection-class](#).

`ws` The workspace name

```
datashield.workspace_save
```

Save DataSHIELD R session to a workspace

Description

Save the current state of the DataSHIELD R session in a workspace with the provided name in each data repository. The workspace can be restored on the next [datashield.login](#).

Usage

```
datashield.workspace_save(conns, ws)
```

Arguments

conns	DSConnection-class object or a list of DSConnection-class s.
ws	The workspace name

```
dsAggregate
```

Aggregate data

Description

Aggregate some data from the DataSHIELD R session using a valid R expression. The aggregation expression must satisfy the data repository's DataSHIELD configuration.

Usage

```
dsAggregate(conn, expr, async = TRUE)
```

Arguments

conn	An object that inherits from DSConnection-class .
expr	Expression to evaluate.
async	Whether the result of the call should be retrieved asynchronously. When TRUE (default) the calls are parallelized over the connections, when the connection supports that feature, with an extra overhead of requests.

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsAssignTable(con, "D", "test.CNSIM")
dsAggregate(con, as.symbol("meanDS(D$WEIGHT)"))
dsDisconnect(con)

## End(Not run)
```

dsAssignExpr

*Assign an expression result***Description**

Assign the result of the evaluation of an expression to a symbol the DataSHIELD R session The assignment expression must satisfy the data repository's DataSHIELD configuration.

Usage

```
dsAssignExpr(conn, symbol, expr, async = TRUE)
```

Arguments

conn	An object that inherits from DSConnection-class .
symbol	Name of the R symbol.
expr	A R expression with allowed assign functions calls.
async	Whether the result of the call should be retrieved asynchronously. When TRUE (default) the calls are parallelized over the connections, when the connection supports that feature, with an extra overhead of requests.

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsAssignExpr(con, "C", as.symbol("c(1, 2, 3)"))
dsDisconnect(con)

## End(Not run)
```

dsAssignResource	<i>Assign a resource object</i>
------------------	---------------------------------

Description

Assign a resource object of class 'ResourceClient' from the data repository to a symbol in the DataSHIELD R session. The resource reference to be assigned must exist (i.e. proper permissions apply) for the DataSHIELD user.

Usage

```
dsAssignResource(conn, symbol, resource, async = TRUE)
```

Arguments

conn	An object that inherits from DSConnection-class .
symbol	Name of the R symbol.
resource	Fully qualified name of a resource reference in the data repository.
async	Whether the result of the call should be retrieved asynchronously. When TRUE (default) the calls are parallelized over the connections, when the connection supports that feature, with an extra overhead of requests.

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsAssignResource(con, "D", "test.CNSIM")
dsDisconnect(con)

## End(Not run)
```

dsAssignTable	<i>Assign a data table</i>
---------------	----------------------------

Description

Assign a data table from the data repository to a symbol in the DataSHIELD R session. The table to be assigned must exist (i.e. proper permissions apply) for the DataSHIELD user.

Usage

```
dsAssignTable(
  conn,
  symbol,
  table,
  variables = NULL,
  missings = FALSE,
  identifiers = NULL,
  id.name = NULL,
  async = TRUE
)
```

Arguments

conn	An object that inherits from DSConnection-class .
symbol	Name of the R symbol.
table	Fully qualified name of a table in the data repository.
variables	List of variable names or Javascript expression that selects the variables of a table. See javascript documentation: http://opaldoc.obiba.org/en/latest/magma-user-guide/variable/
missings	If TRUE, missing values will be pushed from data repository to R, default is FALSE.
identifiers	Name of the identifiers mapping to use when assigning entities to R (if supported by the data repository).
id.name	Name of the column that will contain the entity identifiers. If not specified, the identifiers will be the data frame row names. When specified this column can be used to perform joins between data frames.
async	Whether the result of the call should be retrieved asynchronously. When TRUE (default) the calls are parallelized over the connections, when the connection supports that feature, with an extra overhead of requests.

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsAssignTable(con, "D", "test.CNSIM")
dsDisconnect(con)

## End(Not run)
```

dsConnect

Create a connection to a DataSHIELD-aware data repository

Description

Connect to a data repository going through the appropriate authentication procedure. Some implementations may allow you to have multiple connections open, so you may invoke this function repeatedly assigning its output to different objects. The authentication mechanism is left unspecified, so check the documentation of individual drivers for details.

Usage

```
dsConnect(drv, name, restore = NULL, ...)
```

Arguments

drv	an object that inherits from DSDriver-class .
name	Name of the connection, which must be unique among all the DataSHIELD connections.
restore	Workspace name to be restored in the newly created DataSHIELD R session.
...	authentication arguments needed by the data repository instance; these typically include 'username', 'password', 'token', 'host', 'port', 'dbname', etc. For details see the appropriate 'DSDriver'.

See Also

[dsDisconnect](#) to disconnect from a data repository.

Other DSDriver generics: [DSDriver-class](#), [dsGetInfo\(\)](#)

Examples

```
## Not run:
con <- dsConnect(DSOpal::Opal(), "server1", "username", "password", "https://opal.example.org")
con
dsListTables(con)
dsDisconnect(con)

## End(Not run)
```

DSConnection-class	<i>DSConnection class</i>
--------------------	---------------------------

Description

This virtual class encapsulates the connection to a DataSHIELD-aware data repository, and it provides access to data assignments and aggregations etc.

Implementation note

Individual drivers are free to implement single or multiple simultaneous connections.

See Also

Other DS classes: [DSDriver-class](#), [DSObject-class](#), [DSResult-class](#)

Other DSConnection generics: [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dsConnect(DSOpal::Opal(), "server1", "username", "password", "https://opal.example.org")
con
dsDisconnect(con)

## End(Not run)
```

dsDisconnect	<i>Disconnect (close) a connection</i>
--------------	--

Description

This closes the connection, discards all pending work, and frees resources (e.g., memory, sockets).

Usage

```
dsDisconnect(conn, save = NULL)
```

Arguments

conn	An object inheriting from DSConnection-class .
save	Save DataSHIELD session in data repository with provided identifier string.

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsDisconnect(con)

## End(Not run)
```

DSDriver-class	<i>DSDriver class</i>
----------------	-----------------------

Description

Base class for all DataSHIELD-aware data repositories drivers (e.g., Opal, ...). The virtual class 'DSDriver' defines the operations for creating connections.

See Also

Other DS classes: [DSConnection-class](#), [DSObject-class](#), [DSResult-class](#)
 Other DSDriver generics: [dsConnect\(\)](#), [dsGetInfo\(\)](#)

dsFetch	<i>Get the raw result</i>
---------	---------------------------

Description

Wait for the result to be available and fetch the result from a previous assignment or aggregation operation that may have been run asynchronously, in which case it is a one-shot call. When the assignment or aggregation operation was not asynchronous, the result is wrapped in the object and can be fetched multiple times.

Usage

```
dsFetch(res)
```

Arguments

res An object inheriting from [DSResult-class](#).

See Also

Other DSResult generics: [DSResult-class](#), [dsGetInfo\(\)](#), [dsIsCompleted\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsAssignExpr(con, "C", as.symbol("c(1, 2, 3)"))
res <- dsAggregate(con, as.symbol("length(C)"))
length <- dsFetch(res)
dsDisconnect(con)

## End(Not run)
```

dsGetInfo

Get DataSHIELD-aware data repository metadata

Description

Get DataSHIELD-aware data repository metadata

Usage

```
dsGetInfo(dsObj, ...)
```

Arguments

dsObj	An object inheriting from DSObject-class , i.e. DSDriver-class , DSConnection-class , or a DSResult-class .
...	Other arguments to methods.

Value

a named list

Implementation notes

For ‘DSDriver’ subclasses, this should include the version of the package (‘driver.version’) and the version of the underlying client library (‘client.version’).

For ‘DSConnection’ objects this should report the version of the data repository application (‘repo.version’) and its name (‘repo.name’), the database name (‘dbname’), username, (‘username’), host (‘host’), port (‘port’), etc. It MAY also include any other arguments related to the connection (e.g., thread id, socket or TCP connection type). It MUST NOT include the password.

For ‘DSResult’ objects, this should include the R expression being executed (an expression object tailored by the implementation of DSI) and if the query is complete (a result object tailored by the implementation of DSI).

See Also

Other DSDriver generics: [DSDriver-class](#), [dsConnect\(\)](#)

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Other DSResult generics: [DSResult-class](#), [dsFetch\(\)](#), [dsIsCompleted\(\)](#)

dsHasResource	<i>Check remote resource exists</i>
---------------	-------------------------------------

Description

Check if a remote resource reference exists in the data repository. Returns a logical indicating the existence of a remote resource accessible through this connection.

Usage

```
dsHasResource(conn, resource)
```

Arguments

conn	An object that inherits from DSConnection-class .
resource	the resource fully qualified name

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsHasResource(con, "test.CNSIM")
dsDisconnect(con)

## End(Not run)
```

dsHasTable	<i>Check remote table exists</i>
------------	----------------------------------

Description

Check if a remote table exists in the data repository. Returns a logical indicating the existence of a remote table accessible through this connection.

Usage

```
dsHasTable(conn, table)
```

Arguments

conn	An object that inherits from DSConnection-class .
table	the table fully qualified name

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsHasTable(con, "test.CNSIM")
dsDisconnect(con)

## End(Not run)
```

dsIsAsync	<i>Asynchronous result support</i>
-----------	------------------------------------

Description

When a [DSResult-class](#) object is returned on aggregation or assignment operation, the raw result can be accessed asynchronously, allowing parallelization of DataSHIELD calls over multiple servers. The returned named list of logicals will specify if asynchronicity is supported for: aggregation operation ('aggregate'), table assignment operation ('assignTable'), resource assignment operation ('assignResource') and expression assignment operation ('assignExpr').

Usage

```
dsIsAsync(conn)
```

Arguments

conn An object that inherits from [DSConnection-class](#).

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsIsAsync(con)
dsDisconnect(con)

## End(Not run)
```

dsIsCompleted	<i>Get whether the operation is completed</i>
---------------	---

Description

Get whether the result from a previous assignment or aggregation operation was completed, either with a successful status or a failed one. This call must not wait for the completion, immediate response is expected. Once the result is identified as being completed, the raw result the operation can be get directly.

Usage

```
dsIsCompleted(res)
```

Arguments

res An object inheriting from [DSResult-class](#).

Value

A logical

See Also

Other DSResult generics: [DSResult-class](#), [dsFetch\(\)](#), [dsGetInfo\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsAssignExpr(con, "C", as.symbol("c(1, 2, 3)"))
res <- dsAggregate(con, as.symbol("length(C)"), async = TRUE)
completed <- dsIsCompleted(res)
while (!completed) {
  Sys.sleep(1)
  completed <- dsIsCompleted(res)
}
length <- dsFetch(res)
dsDisconnect(con)

## End(Not run)
```

dsKeepAlive

Keep a connection alive

Description

As the DataSHIELD sessions are working in parallel, this function helps at keeping idle connections alive while others are working. Any communication failure must be silently processed.

Usage

```
dsKeepAlive(conn)
```

Arguments

conn An object inheriting from [DSConnection-class](#).

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsKeepAlive(con)
dsDisconnect(con)

## End(Not run)
```

dsListMethods	<i>Get the DataSHIELD methods</i>
---------------	-----------------------------------

Description

Get the list of DataSHIELD methods that have been configured on the remote data repository.

Usage

```
dsListMethods(conn, type = "aggregate")
```

Arguments

conn	An object that inherits from DSConnection-class .
type	Type of the method: "aggregate" (default) or "assign".

Value

A data.frame with columns: name, type ('aggregate' or 'assign'), class ('function' or 'script'), value, package, version.

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:  
con <- dbConnect(DSOpal::Opal(), "server1",  
  "username", "password", "https://opal.example.org")  
dsListMethods(con)  
dsDisconnect(con)  
  
## End(Not run)
```

dsListPackages	<i>Get the DataSHIELD packages</i>
----------------	------------------------------------

Description

Get the list of DataSHIELD packages with their version, that have been configured on the remote data repository.

Usage

```
dsListPackages(conn)
```

Arguments

conn An object that inherits from [DSConnection-class](#).

Value

A data.frame with columns: name, version.

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsListPackages(con)
dsDisconnect(con)

## End(Not run)
```

dsListResources	<i>List remote resources</i>
-----------------	------------------------------

Description

List remote resources from the data repository. Returns the unquoted names of remote resources accessible through this connection.

Usage

```
dsListResources(conn)
```

Arguments

conn An object that inherits from [DSConnection-class](#).

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsListResources(con)
dsDisconnect(con)

## End(Not run)
```

dsListSymbols

List symbols

Description

After assignments have been performed, some symbols live in the DataSHIELD R session on the server side.

Usage

```
dsListSymbols(conn)
```

Arguments

conn An object that inherits from [DSConnection-class](#).

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsAssignTable(con, "D", "test.CNSIM")
dsListSymbols(con)
dsDisconnect(con)

## End(Not run)
```

dsListTables

List remote tables

Description

List remote tables from the data repository. Returns the unquoted names of remote tables accessible through this connection.

Usage

```
dsListTables(conn)
```

Arguments

conn An object that inherits from [DSConnection-class](#).

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsListTables(con)
dsDisconnect(con)

## End(Not run)
```

dsListWorkspaces	<i>Get the DataSHIELD workspaces</i>
------------------	--------------------------------------

Description

Get the list of DataSHIELD workspaces, that have been saved on the remote data repository.

Usage

```
dsListWorkspaces(conn)
```

Arguments

conn An object that inherits from [DSConnection-class](#).

Value

A data.frame with columns: name, lastAccessDate, size.

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsListWorkspaces(con)
dsDisconnect(con)

## End(Not run)
```

DSLoginBuilder	<i>DataSHIELD login details builder</i>
----------------	---

Description

DataSHIELD login details builder

DataSHIELD login details builder

Format

A R6 object of class DSLoginBuilder

Details

Helper class for creating a valid data frame that can be used to perform `datashield.login`. See also `newDSLoginBuilder`.

Methods

Public methods:

- `DSLoginBuilder$new()`
- `DSLoginBuilder$append()`
- `DSLoginBuilder$build()`
- `DSLoginBuilder$clone()`

Method `new()`: Create a new `DSLoginBuilder` instance.

Usage:

```
DSLoginBuilder$new(logins = NULL, .silent = FALSE)
```

Arguments:

`logins` A valid login details data frame to initiate the builder, optional.

`.silent` Do not warn user when non secure HTTP urls are encountered. Default is FALSE.

Returns: A `DSLoginBuilder` object.

Method `append()`: Append login information for a specific server.

Usage:

```
DSLoginBuilder$append(  
  server,  
  url,  
  table = "",  
  resource = "",  
  driver = "OpalDriver",  
  user = "",  
  password = "",  
  token = "",  
  options = ""  
)
```

Arguments:

`server` The server name (must be unique).

`url` The url to connect to the server or a R symbol name.

`table` The table path that identifies the dataset in the server.

`resource` The resource path that identifies the resource reference in the server.

`driver` The `DSDriver-class` name to build the `DSConnection-class`.

`user` The user name in the user credentials.

`password` The user password in the user credentials.

`token` The personal access token (ignored when user credentials are not empty).

`options` Any options (R code to be parsed) that could be relevant for the DS connection object.

Method `build()`: Build the DSLoginBuilder instance.

Usage:

`DSLoginBuilder$build()`

Returns: The DataSHIELD logindata data.frame

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`DSLoginBuilder$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

DSObject-class

DSObject class

Description

Base class for all other DataSHIELD classes (e.g., drivers, connections). This is a virtual Class: No objects may be created from it.

Details

More generally, DataSHIELD defines a very small set of classes and generics that allows users and applications perform meta-analysis with a common interface. The virtual classes are ‘DSDriver’ that individual drivers extend, ‘DSConnection’ that represent instances of DataSHIELD-aware data repository connections, and ‘DSResult’ that represent the result of a DataSHIELD operation. These three classes extend the basic class of ‘DSObject’, which serves as the root or parent of the class hierarchy.

Implementation notes

An implementation MUST provide methods for the following generics:

- [dsGetInfo](#)

It MAY also provide methods for:

- [summary](#) Print a concise description of the object. The default method invokes ‘dsGetInfo(dsObj)’ and prints the name-value pairs one per line. Individual implementations may tailor this appropriately.

See Also

Other DS classes: [DSConnection-class](#), [DSDriver-class](#), [DSResult-class](#)

Examples

```
## Not run:
drv <- DSOpal::Opal()
con <- dsConnect(drv, "username", "password", "https://opal.example.org")

rs <- dsAssign(con, "Project.TableA")
is(drv, "DSObject") ## True
is(con, "DSObject") ## True
is(rs, "DSObject")  ## True

dsDisconnect(con)

## End(Not run)
```

DSResult-class

DSResult class

Description

This virtual class describes the result and state of execution of a DataSHIELD request (aggregation or assignment).

Implementation notes

Individual drivers are free to allow single or multiple active results per connection.

The default show method displays a summary of the query using other DS generics.

See Also

Other DS classes: [DSConnection-class](#), [DSDriver-class](#), [DSObject-class](#)

Other DSResult generics: [dsFetch\(\)](#), [dsGetInfo\(\)](#), [dsIsCompleted\(\)](#)

dsRmSymbol

Remove a symbol

Description

After removal, the data identified by the symbol will not be accessible in the DataSHIELD R session on the server side.

Usage

```
dsRmSymbol(conn, symbol)
```

Arguments

conn An object that inherits from [DSConnection-class](#).
symbol Name of the R symbol.

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmWorkspace\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsAssignTable(con, "D", "test.CNSIM")
dsRmSymbol(con, "D")
dsDisconnect(con)

## End(Not run)
```

dsRmWorkspace	<i>Remove a DataSHIELD workspace</i>
---------------	--------------------------------------

Description

Remove a DataSHIELD workspace from the remote data repository. Ignore if no such workspace exists.

Usage

```
dsRmWorkspace(conn, name)
```

Arguments

conn An object that inherits from [DSConnection-class](#).
name Name of the workspace

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsSaveWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsSaveWorkspace(con, "foo")
dsListWorkspaces(con)
dsRmWorkspace(con, "foo")
dsListWorkspaces(con)
dsDisconnect(con)

## End(Not run)
```

dsSaveWorkspace	<i>Save the DataSHIELD R session in a workspace</i>
-----------------	---

Description

Save the DataSHIELD R session in a workspace on the remote data repository.

Usage

```
dsSaveWorkspace(conn, name)
```

Arguments

conn	An object that inherits from DSConnection-class .
name	Name of the workspace

See Also

Other DSConnection generics: [DSConnection-class](#), [dsAggregate\(\)](#), [dsAssignExpr\(\)](#), [dsAssignResource\(\)](#), [dsAssignTable\(\)](#), [dsDisconnect\(\)](#), [dsGetInfo\(\)](#), [dsHasResource\(\)](#), [dsHasTable\(\)](#), [dsIsAsync\(\)](#), [dsKeepAlive\(\)](#), [dsListMethods\(\)](#), [dsListPackages\(\)](#), [dsListResources\(\)](#), [dsListSymbols\(\)](#), [dsListTables\(\)](#), [dsListWorkspaces\(\)](#), [dsRmSymbol\(\)](#), [dsRmWorkspace\(\)](#)

Examples

```
## Not run:
con <- dbConnect(DSOpal::Opal(), "server1",
  "username", "password", "https://opal.example.org")
dsSaveWorkspace(con, "foo")
dsListWorkspaces(con)
dsDisconnect(con)

## End(Not run)
```

newDSLoginBuilder *Create a new DataSHIELD login details builder*

Description

Shortcut function to create a new [DSLoginBuilder](#) instance. The data frame that is being built can be used to perform [datashield.login](#).

Usage

```
newDSLoginBuilder(logins = NULL, .silent = FALSE)
```

Arguments

logins	A valid login details data frame to initiate the builder, optional.
.silent	Do not warn user when non secure HTTP urls are encountered. Default is FALSE.

Examples

```
{
  builder <- newDSLoginBuilder()
  builder$append(server="server1", url="https://opal-demo.obiba.org", table="datashield.CNSIM1",
    user="administrator", password="password")
  builder$append(server="server2", url="dslite.server", table="CNSIM2")
  builder$append(server="server3", url="http://molgenis.example.org", table="CNSIM3",
    token="123456789")
  builder$append(server="server4", url="dslite.server", table="CNSIM4")
  logindata <- builder$build()
}
```

Index

- * **Connections management**
 - datashield.connections, 8
 - datashield.connections_default, 9
 - datashield.connections_find, 10
- * **DS classes**
 - DSCConnection-class, 25
 - DSDriver-class, 26
 - DSObject-class, 38
 - DSResult-class, 39
- * **DSCConnection generics**
 - dsAggregate, 20
 - dsAssignExpr, 21
 - dsAssignResource, 22
 - dsAssignTable, 23
 - DSCConnection-class, 25
 - dsDisconnect, 25
 - dsGetInfo, 27
 - dsHasResource, 28
 - dsHasTable, 29
 - dsIsAsync, 29
 - dsKeepAlive, 31
 - dsListMethods, 32
 - dsListPackages, 33
 - dsListResources, 33
 - dsListSymbols, 34
 - dsListTables, 35
 - dsListWorkspaces, 36
 - dsRmSymbol, 39
 - dsRmWorkspace, 40
 - dsSaveWorkspace, 41
- * **DSDriver generics**
 - dsConnect, 24
 - DSDriver-class, 26
 - dsGetInfo, 27
- * **DSResult generics**
 - dsFetch, 26
 - dsGetInfo, 27
 - dsIsCompleted, 30
 - DSResult-class, 39
- datashield.aggregate, 3
- datashield.assign, 4
- datashield.assign.expr, 5
- datashield.assign.resource, 6
- datashield.assign.table, 4, 7
- datashield.connections, 8, 8, 10
- datashield.connections_default, 8, 9, 9, 10
- datashield.connections_find, 9, 10, 10
- datashield.errors, 11
- datashield.login, 6, 7, 11, 16, 18, 20, 37, 42
- datashield.logout, 13
- datashield.method_status, 14
- datashield.methods, 14
- datashield.pkg_check, 15
- datashield.pkg_status, 15
- datashield.resource_status, 16
- datashield.resources, 16
- datashield.rm, 17
- datashield.symbols, 17
- datashield.table_status, 18
- datashield.tables, 18
- datashield.workspace_rm, 19
- datashield.workspace_save, 20
- datashield.workspaces, 19
- dsAggregate, 20, 21–23, 25, 26, 28–36, 40, 41
- dsAssignExpr, 20, 21, 22, 23, 25, 26, 28–36, 40, 41
- dsAssignResource, 20, 21, 22, 23, 25, 26, 28–36, 40, 41
- dsAssignTable, 20–22, 23, 25, 26, 28–36, 40, 41
- dsConnect, 24, 26, 28
- DSCConnection-class, 25
- dsDisconnect, 20–25, 25, 28–36, 40, 41
- DSDriver-class, 26
- dsFetch, 26, 28, 30, 39
- dsGetInfo, 20–27, 27, 28–36, 38–41
- dsHasResource, 20–23, 25, 26, 28, 28, 29–36,

40, 41
dsHasTable, *20–23, 25, 26, 28, 29, 30–36, 40, 41*
dsIsAsync, *20–23, 25, 26, 28, 29, 29, 31–36, 40, 41*
dsIsCompleted, *27, 28, 30, 39*
dsKeepAlive, *20–23, 25, 26, 28–30, 31, 32–36, 40, 41*
dsListMethods, *20–23, 25, 26, 28–31, 32, 33–36, 40, 41*
dsListPackages, *20–23, 25, 26, 28–32, 33, 34–36, 40, 41*
dsListResources, *20–23, 25, 26, 28–33, 33, 34–36, 40, 41*
dsListSymbols, *20–23, 25, 26, 28–34, 34, 35, 36, 40, 41*
dsListTables, *20–23, 25, 26, 28–34, 35, 36, 40, 41*
dsListWorkspaces, *20–23, 25, 26, 28–35, 36, 40, 41*
DSLoginBuilder, *36, 42*
DSObject-class, *38*
DSResult-class, *39*
dsRmSymbol, *20–23, 25, 26, 28–36, 39, 40, 41*
dsRmWorkspace, *20–23, 25, 26, 28–36, 40, 40, 41*
dsSaveWorkspace, *20–23, 25, 26, 28–36, 40, 41*

newDSLoginBuilder, *37, 42*

summary, *38*