

Package ‘mortyr’

January 10, 2021

Title Wrapper to 'The Rick and Morty' API

Version 0.0.2

Description Returns information about characters, locations, and episodes from 'The Rick and Morty' API: <<https://rickandmortyapi.com>>.

License MIT + file LICENSE

URL <https://github.com/mikejohnpage/mortyr>

BugReports <https://github.com/mikejohnpage/mortyr/issues>

Encoding UTF-8

LazyData true

Imports httr, jsonlite, tibble

Suggests testthat

RoxygenNote 7.1.1

NeedsCompilation no

Author Michael Page [aut, cre]

Maintainer Michael Page <hello@mikejohnpage.com>

Repository CRAN

Date/Publication 2021-01-10 14:30:08 UTC

R topics documented:

| | |
|--------------------------|---|
| get_characters | 2 |
| get_episodes | 3 |
| get_locations | 3 |

| | |
|--------------|----------|
| Index | 5 |
|--------------|----------|

`get_characters`*Get characters*

Description

`get_characters` returns a tibble of all the characters from the 'character' endpoint of [The Rick and Morty API](#). This information includes:

- id
- name
- status
- species
- type
- gender
- image
- episode
- url
- created
- origin.name
- origin.url
- location.name
- location.url

Usage

```
get_characters()
```

Examples

```
## Not run:  
get_characters()  
  
## End(Not run)
```

| | |
|--------------|---------------------|
| get_episodes | <i>Get episodes</i> |
|--------------|---------------------|

Description

get_episodes returns a tibble of all the episodes from the 'episode' endpoint of **The Rick and Morty API**. This information includes:

- id
- name
- air_date
- episode
- characters
- url
- created

Usage

```
get_episodes()
```

Examples

```
## Not run:  
get_episodes()  
  
## End(Not run)
```

| | |
|---------------|----------------------|
| get_locations | <i>Get locations</i> |
|---------------|----------------------|

Description

get_locations returns a tibble of all the locations from the 'location' endpoint of **The Rick and Morty API**. This information includes:

- id
- name
- type
- dimension
- residents
- url
- created

Usage

```
get_locations()
```

Examples

```
## Not run:  
get_locations()  
  
## End(Not run)
```

Index

`get_characters`, 2
`get_episodes`, 3
`get_locations`, 3